

BIO BRICK 2.0

Bio Brick 2.0 contains more strains and a higher concentration of cells than our original formula to effectively enhance your wastewater treatment system's biological performance. Our special blend of bacteria, nutrients, and surface tension suppressants work to break down grease and organic solids, reduce sludge build-up and eliminate malodours. Now available in 4 new sizes!

CODE: ENV-2003




USAGE

Suspend the Bio Brick in the treatment area so that it will be fully covered in water at all times.

Place in an area of low flow; product life may be shortened considerably if placed in a high flow area.

Replace when product is exhausted. Product lifespan depends on brick size and flow.



APPLICATIONS

- Lift Stations
- Septic Systems
- Grease Traps

PROGRESSIVE SCIENCE



Strain A

- High performing strain produces enzymes that efficiently breakdown polymers, proteins, carbohydrates, fats and oils



Strain B

- Active at pH levels as low as 4.25
- Facultative



Strain C

- Tolerant to toxins and areas of high contamination



Strain D

- Demonstrates cellulase and anti-fungal activity
- Salt tolerant



Strain E

- Produces biosurfactants to reduce surface and interfacial tension
- Grows at temperatures as low as 4°C



Safe and effective cleaning products can be made completely cruelty-free. We perform no animal testing and none of our ingredients contain animal products or by-products.

WHAT DOES BIOBRICK DO?

- Reduces wear and tear on pumps and infrastructure
- Reduces sludge build-up
- Enhances BOD / COD removal
- Provides automated maintenance dosages wherever regular Envirozyme treatment cannot be applied



EnviroWay
CLEAN YOUR WORLD





www.enviroway.ca

2241 Hanselman Ave. Saskatoon, SK S7L 6A7

306-244-7727

TF 1-888-274-0862

SPECIFICATIONS

Physical Form	Solid
Colour	Orange/Red
Fragrance	Musty
pH (1 g/L solution)	6-8
Working pH	6-9

STORAGE AND HANDLING



Store in a dry, cool place.



Store away from harsh chemicals.
Keep out of reach of children.

SHELF LIFE: minimum 2 years

PRECAUTIONS

Wash hands thoroughly with warm, soapy water after handling.

For more information or Safety Data Sheets (SDS) please contact us or see our website.

PACKAGING

AVAILABLE IN:

Item Code	Brick Size	Lift Station Size	Product Lifespan
ENV-2003B	5LB	50 – 150 Gal	45 – 75 days
ENV-2003C	10LB	250 - 500 Gal	60 – 90 days
ENV-2003D	30 LB	1000 - 2000 Gal	100 – 120 days

Please note that product lifespan will vary based on flow rates.

QUESTIONS?

Contact us!

Email: techteam@enviroway.net

Phone: (306) 244-7727